



FF521BL7SSHADA



32.5" x 19.25" x 21.38" (H x W x D)

Commercially listed ADA Compliant 20" wide counter height all-refrigerator, auto defrost with a lock, stainless steel door, horizontal handle, and black cabinet

Highlights:

- Freestanding all-refrigerator offers full 4.1 cu.ft. capacity
- ETL-S listed for commercial use
- 32" height for use in ADA compliant settings

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use
ADA compliant	32" high meets ADA guidelines
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Fully finished black cabinet	Allows the unit to be used freestanding
Factory installed lock	Top-mounted for convenient security
Stainless steel wrapped door	Durable 304 grade wrapping
Professional horizontal handle	Thin 14mm diameter on stainless steel handle, mounted horizontally on the door
Automatic defrost	Reduced maintenance with auto defrost system
Adjustable glass shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup



FF521BL7SSHHADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.5" (83 cm)
Width	19.25" (49 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	4.1 cu.ft. (116 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	64.0 lbs. (29 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101040233

Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Crisper Qty	1
Crisper Finish	Transparent
Crisper Cover	Glass
Shelf Type	Glass
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.75oz.
High Side PSI	205.0
Low Side PSI	103.0
Level Legs Qty	2
Interior Light	Yes

Dimensions	
Interior Height	28.5" (72 cm)
Interior Width	15.75" (40 cm)
Interior Depth	18.0" (46 cm)

Compressor Step Height	8.0" (20 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	6.75" (17 cm)

