accuc@ld

FF7LBISSHVADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in undercounter all-refrigerator for general purpose or commercial use, auto defrost w/lock, SS door, thin handle, and white cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercially approved for use in foodservice establishments

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

32 inch height fits under standard ADA counters
ETL-S listed to NSF-7 Standards for use in commercial establishments
Less than 24 inches wide with a full 5.5 c.f. capacity
Make the best use of space by installing your appliance under the counter and flush with other cabinets
Allows the refrigerator to be used freestanding
Keyed lock for a secure interior
Durable design with lasting elegance
Thin 14mm diameter on vertical stainless steel handle
Reduced user maintenance with automatic defrost





accuc@ld

FF7LBISSHVADA Specifications:

Height of Cabinet 32.0" (81 cr Height to Hinge Cap 32.25" (82 cr Width 23.63" (60 cr Depth 23.5" (60 cr Depth with Handle 24.75" (63 cr Depth with door at 90° 45.5" (116 cr Capacity 5.5 cu.ft. (156 Defrost Type Automat Door Stainless Ste Cabinet Whi	m) m) m) m) m) m)
Width 23.63" (60 cr Depth 23.5" (60 cr Depth with Handle 24.75" (63 cr Depth with door at 90° 45.5" (116 cr Capacity 5.5 cu.ft. (156 Defrost Type Automat Door Stainless Ste	m) m) m) m) L)
Depth 23.5" (60 cr Depth with Handle 24.75" (63 cr Depth with door at 90° 45.5" (116 cr Capacity 5.5 cu.ft. (156 Defrost Type Automat Door Stainless Ste	m) m) m) L)
Depth with Handle 24.75" (63 cr Depth with door at 90° 45.5" (116 cr Capacity 5.5 cu.ft. (156 Defrost Type Automat Door Stainless Ste	m) m) L)
Depth with door at 90° 45.5" (116 cr Capacity 5.5 cu.ft. (156 Defrost Type Automat Door Stainless Ste	n) L)
Capacity 5.5 cu.ft. (156 Defrost Type Automat Door Stainless Ste	L)
Defrost Type Automat Door Stainless Ste	
Door Stainless Ste	tic
Cabinet Whi	el
	ite
US Electrical Safety	JL
Canadian Electrical UL Safety	.C
Sanitation ETL-	-S
Amps 1	.3
Voltage/Frequency 115 V AC/60 H	Ηz
Weight 100.0 lbs. (45 k	.g)
Shipping Weight 105.0 lbs. (48 k	.g)
Parts & Labor Warranty 1 Ye	ar
Compressor Warranty 5 Year	rs
UPC 76110103624	43
Refrigerator Features	
Door Swing RH	ID
Reversible Factory Reversib	ole
Shelf Type Wi	re
Shelf Qty	3
Adjustable Shelves Ye	es
Thermostat Type Di	ial
Refrigerant Type R134	— 4а
Refrigerant Amount 1.80	Z.
High Side PSI 285	.0
Low Side PSI 88	3.0
Level Legs Qty	4
Level Legs Qty	4 es
Level Legs Qty	
Level Legs Qty Interior Light Ye	es
Level Legs Qty Interior Light Ye Dimensions	es m)

Compressor Step Height	5.5" (14 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)



