

FS20L7FROST



22.25" x 19.75" x 21" (H x W x D)

DISCONTINUED: Replaced by the FS22L7FROST

Highlights:

Commercially approved and CalCode compliant

Precise temperature management with a digital thermostat

Factory-installed lock for security you can count on

Product Features:

24° F pre-set operation	Ideal temperature to hold aluminum bottled beer just above its freezing point
Commercially approved	ETL-S listed to NSF-7 for use in foodservice establishments
Digital thermostat	Precise temperature management at the touch of a button
Compact dimensions	20 inch footprint in cube shape fits easily above counters
FROSTED decal	Choose from an English or Spanish decal over the front door
Factory installed lock	Keep contents secure with a front lock on the door
Fully finished white cabinet	Allows the unit to be used freestanding
Reversible door	Keep your options flexible with a reversible door that is easy to switch when your arrangement changes
Manual defrost	Static and stable cooling with no internal fans

FS20L7FROST Specifications:

Overview	
Height of Cabinet	22.25" (57 cm)
Width	19.75" (50 cm)
Depth	21.0" (53 cm)
Depth with Handle	21.0" (53 cm)
Depth with door at 90°	39.5" (100 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	Decal
Cabinet	White
US Electrical Safety	UL
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	55.0 lbs. (25 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Type	Wire
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

