# accucold

# **FS408BLBIFRADA**



#### 32.5" x 19.25" x 21.38" (H x W x D)

ADA Compliant 20" wide built-in undercounter all-freezer, -20° C capable with a lock and stainless steel door frame for slide-in custom panels

#### **Highlights:**

32" height fits under lower ADA compliant counters

Flexible design allows built-in or freestanding use in 20" wide spaces

-20º C capable with interior slide-out drawers for easy storage

### **Product Features:**

32" high to fit under lower ADA compliant counters
2.8 cu.ft. capacity inside a slim footprint
Make the best use of space by installing your appliance under the counter
Allows the unit to be used freestanding
Top-mounted for convenient security
Two-piece "U"-shaped door frame accepts slide-in custom panels (panel size: 19 1/4" W x 31 $1/4$ " H at up to 1/4" thick)
Keep your options flexible with a reversible door that is easy to switch when your arrangement changes
Efficient performance with reliable temperature stability
Low temperature capability ideal for certain sensitive items

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 $\checkmark$ 



# accuceld

## FS408BLBIFRADA Specifications:

Height of Cabinet32.0" (81 cm)Height to Hinge Cap32.5" (83 cm)Width19.25" (49 cm)Depth21.38" (54 cm)Depth with door at 90°39.5" (100 cm)Capacity2.8 cu.ft. (79 L)Defrost TypeManualDoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical Safety1.6
Width19.25" (49 cm)Depth21.38" (54 cm)Depth with door at 90°39.5" (100 cm)Capacity2.8 cu.ft. (79 L)Defrost TypeManualDoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-C
Depth21.38" (54 cm)Depth with door at 90°39.5" (100 cm)Capacity2.8 cu.ft. (79 L)Defrost TypeManualDoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-C
Depth with door at 90°39.5" (100 cm)Capacity2.8 cu.ft. (79 L)Defrost TypeManualDoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-C
Capacity2.8 cu.ft. (79 L)Defrost TypeManualDoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-C
Defrost TypeManualDoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-C
DoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-C
Cabinet Black   US Electrical Safety ETL   Canadian Electrical Safety ETL-C
US Electrical Safety ETL Canadian Electrical Safety ETL-C
Canadian Electrical Safety ETL-C
· · · · · · · · · · · · · · · · · · ·
Amps 1.6
•
Voltage/Frequency 115 V AC/60 Hz
Weight 64.0 lbs. (29 kg)
Shipping Weight 67.0 lbs. (30 kg)
Parts & Labor Warranty 1 Year
Compressor Warranty 5 Years
UPC 761101041766
Freezer
Door Swing RHD
Reversible Yes
Interior Height 26.38" (67 cm)
Interior Width 14.0" (36 cm)
Interior Depth 16.75" (43 cm)
Thermostat Type Dial
Refrigerant Type R134a
Refrigerant Amount 3.0 oz.
High Side PSI 210.0
Low Side PSI 105.0
Level Legs 2
Interior Drawers Yes
Drawers Qty 4



