

SCR600BLADA



32.38" x 23.63" x 23.5" (H x W x D)

ADA compliant, commercially approved glass door beverage center with black cabinet and front lock

Highlights:

UNAVAILABLE AT THIS TIME

Commercially approved for use in food service establishments

32 inches high to meet ADA guidelines for lower counter height

Product Features:

Commercially approved	ETL-S Listed and CalCode Compliant
ADA Compliant	32 inch height is designed to meet ADA guidelines for lower counter height
Factory installed lock	Keyed lock for a secure interior
Fully finished black cabinet	Allows the unit to be used freestanding
Double pane tempered glass door	Heat resistant design provides clear view of stored products, with an elegant trim in brushed aluminum
Reversible door	Keep placement options flexible with a reversible door swing that is easy to switch when your arrangement changes
Automatic defrost	Reduced user maintenance with automatic defrost
Adjustable glass shelves	Rearrange the refrigerator space to fit any sized item or remove shelves for simple cleanup
Hidden evaporator	SUMMIT's "hidden" evaporator is concealed in the wall so it never touches your food or fingers



SCR600BLADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.38" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.38" (64 cm)
Depth with door at 90°	45.63" (116 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Glass
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.3
Shipping Weight	120.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101019208
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Glass
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	1.8oz.
High Side PSI	285.0
Low Side PSI	70.0
Level Legs Qty	4
Interior Light	Yes
Dimensions	
Interior Height	26.0" (66 cm)
Interior Width	20.75" (53 cm)
Interior Depth	17.5" (44 cm)
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	20.75" (53 cm)

Compressor Step Depth 5.0"

