accuc@ld

CM4057SSHV



34" x 19.25" x 21.38" (H x W x D)

Commercially listed 20" wide counter height refrigeratorfreezer with stainless steel door, thin handle, and white cabinet

Highlights:

ETL-S listed for commercial use

Slim 20" width is ideal for any setting

Professional style with 304 grade stainless steel wrapped door and sleek handle

Product Features:

Commercially listed	ETL-S listed to NSF standards for commercial use
Slim 20" width	Full 4.1 cu.ft. capacity inside conveniently slim footprint
Fully finished white cabinet	Allows the unit to be used freestanding
Stainless steel wrapped door	Durable 304 grade wrapping
Professional handle	Thin 14mm diameter on vertical stainless steel handle
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Manual defrost	Efficient performance with reliable temperature stability
Adjustable shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup
Crisper drawer	Get the longest life and best taste out of produce by storing greens in a bottom crisper

accuc@ld

CM4057SSHV Specifications:

Overview		
Height of Cabinet	33.5" (85 cm)	
Height to Hinge Cap	34.0" (86 cm)	
Width	19.25" (49 cm)	
Depth	21.38" (54 cm)	
Depth with door at 90°	39.5" (100 cm)	
Capacity	4.1 cu.ft. (116 L)	
Defrost Type	Manual	
Door	Stainless Steel	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Energy Usage/Year	339.0kWh/year	
Amps	1.4	
Voltage/Frequency	115 V AC/60 Hz	
Weight	64.0 lbs. (29 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101030944	
Refrigerator-Freezer		
Door Swing	RHD	
Reversible	Factory Reversible	
Adjustable Shelves	Yes	
Crisper Qty	1	
Crisper Finish	Transparent	
Crisper Cover	Glass	
Interior Light	Yes	
Refrigerator - Interior Height	28.75" (73 cm)	
Refrigerator - Interior Width	15.75" (40 cm)	
Refrigerator - Interior Depth	17.75" (45 cm)	
Refrigerator - Shelf Type	Wire	
Refrigerator - Shelf Qty	2	
Thermostat Type	Dial	
Refrigerant Type	R134a	

High Side PSI	205.0
Low Side PSI	103.0
Level Legs	2
Wheels	2



