

# VT65MLBI7PLUS2



33.5" x 23.63" x 23.5" (H x W x D)

Commercially approved 24" wide all-freezer for built-in use, manual defrost with a NIST calibrated thermometer, lock, and -25°C capability

### Highlights:

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24 wide spaces

Factory installed lock provides security you can count on

### Product Features:

Commercially approved	ETL-S listed to NSF-7 commercial standards
Slim undercounter dimensions	Less than 24 wide to fit tight spaces
Built-in capable	Make the best use of space by installing your appliance under the counter
NIST calibrated temperature display	Thermometer provides continuous display of the current and high/low temperature to the nearest tenth of a degree, with a readout switchable from Celsius to Fahrenheit at the touch of a button
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of refrigerator air temperature
Factory installed lock	Keyed lock for secure interior
Manual defrost	Efficient performance with reliable temperature stability
-25°C capable	Low temperature capability ideal for certain sensitive items
Pull-out drawers	Clear baskets for convenient and separated storage

## VT65MLBI7PLUS2 Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101058009

Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Height Adjustable	1
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	4
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.0" (15 cm)
Compressor Step Width	17.75" (45 cm)
Compressor Step Depth	6.0" (15 cm)

### Temperature Range

