accuc@ld

FF7LWCSSADA



32.25" x 23.75" x 23.25" (H x W x D)

ADA compliant built-in undercounter all-refrigerator for general purpose or commercial use, auto defrost w/SS wrapped exterior, towel bar handle, and lock

Highlights:

Commercially approved for use in foodservice establishments

32" height allows installation under lower ADA compliant counters

Complete stainless steel construction adds luxury to any setting

Product Features:

ETL-S listed to NSF-7 Standards for use in commercial establishments
32 inch height fits under standard ADA counters
Ideal 24" footprint offers full 5.5 cu.ft. storage capacity in a slim fit
Make the best use of space by installing your appliance under the counter and flush with other cabinets
Allows the refrigerator to be used freestanding
Keyed lock for a secure interior
Durable design with lasting elegance
Curved handle in brushed stainless steel offers a sturdy grip with professional elegance
Reduced user maintenance with automatic defrost



accuc@ld

FF7LWCSSADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.75" (60 cm)
Depth	23.25" (59 cm)
Depth with Handle	25.25" (64 cm)
Depth with door at 90°	45.5" (116 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	150.0 lbs. (68 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101072586
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Dial
Fan Type	Exterior
Refrigerant Type	R600a
Refrigerant Amount	0.64oz.
3	
High Side PSI	180.0
	180.0 80.0
High Side PSI	
High Side PSI Low Side PSI	80.0
High Side PSI Low Side PSI Level Legs Qty	80.0
High Side PSI Low Side PSI Level Legs Qty Interior Light	80.0

Interior Depth	17.5" (44 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	6.0" (15 cm)



