SUMMIT

HC24WW



5.5" x 23.88" x 20" (H x W x D)

24 inch wide under cabinet convertible range hood for ducted or ductless use in white, made in North America

Highlights:

24 inch wide pairs well with a variety of ranges and cooktops

Made in North America in a TAA designated country

Steel construction for lasting durability

Product Features:

| Under cabinet range hood | Low profile design offers classic style to finish your kitchen | |
|-------------------------------------|--|--|
| 24 inch width | Sized for use over 24 inch cooking surfaces (additional sizes available) | |
| Convertible design | Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible | |
| White finish | Matte finish in white suits any kitchen space | |
| Easy conversion | Ships pre-set for recirculating mode but can be converted in a few simple steps | |
| Versatile top or rear exhaust | Can be connected to 3 1/4" x 10" vertical or horizontal exterior venting or 7" round vertical (transition required for both) | |
| Powerful ventilation | Can operate at 270 CFM to ensure thorough ventilation of your cooking surface | |
| Angled airflow | Vents are set at a slight upwards angle, ensuring smoke and odors won't be directed towards the user | |
| Durable 21 gauge steel construction | Powder-coated finish over steel that's 53% heavier gauge than most of the industry's under cabinet hoods | |



HC24WW Specifications:

| Overview | | |
|-------------------------------|--|--|
| Height of Cabinet | 5.5" (14 cm) | |
| Width | 23.88" (61 cm) | |
| Depth | 20.0" (51 cm) | |
| Cabinet | White | |
| US Electrical Safety | UL | |
| Canadian Electrical Safety | ULC | |
| Amps | 1.7 | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Weight | 12.0 lbs. (5 kg) | |
| Parts & Labor Warranty | 1 Year | |
| UPC | 761101087092 | |
| Range Hood | | |
| Installation | Under Cabinet | |
| Venting | Convertible | |
| Controls | Dial | |
| Number of Fan Speeds | 2 | |
| Maximum Air Movement | 270.0 CFM | |
| Sone Rating | 6 | |
| Duct Shape | 3"1/4" x 10" rectangular or 6/7" round with transition | |

